

SG Series Spin-Glas®

Fiber Glass Insulation

Description

SG Series Spin-Glas® appliance insulation is an efficient thermal and acoustical blanket made from rotary-process glass fibers bonded with a thermosetting resin.

The range of density and thickness of SG Series Spin-Glas permits the optimization of thermal, acoustical, and space requirements. These resilient fiber glass blankets resist damage and are easily cut with a knife, shear, or steel rule die. The blankets do not contribute to or absorb odors and carry UL Fire Hazard Classification 25/50. The insulation readily conforms to curved and irregular shapes.

Applications

This product was developed specifically for freezers, refrigerators, and other low and medium temperature appliances operating up to 350°F (177° C). Also ideal for use in double-wall HVAC equipment.

Available Forms

SG Series Spin-Glas is available in rolls in a wide range of thicknesses and densities (see back of this sheet). Densities are adjusted to meet thermal conductivity requirements.

Custom Fabrication

In addition to standard dimensions, a Johns Manville Approved Fabricator can provide specially cut shapes and pieces to particular customer specifications.



Fabricated Products

SG Series Spin-Glas insulation is manufactured to specific customer width requirements. Contact your Johns Manville sales representative for limitations. Die-cut or fabricated pieces are generally supplied by strategically located Johns Manville fabricators, specially equipped to provide prompt service to manufacturers in their areas.

Applications

- Refrigerators and Freezers
- Transportation
- Water Heater Retrofit Kits
- Dishwashers
- HVAC Equipment
- Other Appliances

Specifications

Temperature Limit	350°F (177°C)
Fire Hazard Classification (FHC)	25/50 (per ASTM E 84 and UL 723 and CAN/ULC S102 -M88). Labels supplied when requested on order. Meets NFPA 90A and 90B.

Thermal Conductivity (k) Per ASTM C 518

Type	Density		75°F (24°C) Mean Temp.	
	pcf	kg/m ³	Btu•in/(hr•ft ² •°F)	W/m•°C
SG-28	0.85	14	0.27	.039
SG-26	1.04	17	0.26	.037
SG-25	1.20	19	0.25	.036
SG-24	1.56	25	0.24	.035
SG-23	1.78	29	0.24	.035
SG-22	2.20	35	0.23	.033

Acoustical Performance

Type "A" Mounting Sound Absorption Coefficients*

Type	Thickness		Frequency (Hz)							NRC**
	in.	mm	125	250	500	1000	2000	4000		
SG-28	1	25	0.11	0.31	0.60	0.80	0.90	0.93	0.65	
	2	51	0.16	0.60	0.92	0.98	0.97	1.01	0.85	
	3	76	0.36	1.02	1.12	1.10	1.08	1.07	1.10	
SG-26	1	25	0.09	0.30	0.60	0.77	0.89	0.93	0.65	
	2	51	0.18	0.64	0.99	1.02	1.01	1.04	0.90	
	3	76	0.36	0.99	1.20	1.11	1.06	1.06	1.10	
SG-24	1	25	0.10	0.28	0.62	0.84	0.95	0.97	0.65	
	2	51	0.22	0.71	1.03	1.08	1.05	1.02	0.95	
SG-22	1	25	0.05	0.23	0.61	0.90	1.00	1.01	0.70	

*Tested in accordance with ASTM C 423 90a and ASTM E 795 83

**Noise Reduction Coefficient

SG Series Spin-Glas®

Fiber Glass Insulation



Johns Manville

717 17th St.
Denver, CO 80202
(800) 654-3103
www.jm.com

Insulation Systems, OEM Insulations

Eastern Region

P.O. Box 158
Defiance, OH 43512
(800) 426-2435
Fax: (800) 329-7397

Western Region & Canada

P.O. Box 625005
Littleton, CO 80162
(800) 293-3393
Fax: (800) 741-0183

Technical Information

(800) 458-7198

The physical and chemical properties of SG Series Spin-Glas® Insulation listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Numerical flame spread and smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you to assure current information. **All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions including Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions, Limited Warranty and Limitation of Remedy, and information on other Johns Manville thermal insulations and systems, call (800) 654-3103.**

Printed on recycled paper.

Copyright ©2008 Johns Manville
Printed in USA